

1 / 6 EN

Revision: 08.02.2006 Replaces the version of: 21.07.2005 PDF date: 09.02.2006

ProLine Jet Clean Diesel System Reiniger 500ML

Art.: 5154

Safety Data Sheet according to EC-Regulation 91/155/EEC

1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation

ProLine Jet Clean Diesel System Reiniger 500ML

Art.: 5154

Use of the substance/preparation

Refer to description of material or preparation.

Company/undertaking identification

LIQUI MOLY GmbH, Jerg-Wieland-Straße 4, D-89081 Ulm-Lehr

Telephone (+49) 0731-1420-0, Fax (+49) 0731-1420-88

Emergency telephone / Office for advice

Advisory office in case of poisoning:

Tel.:

Telephone number of the company in case of emergencies:

Tel. (+49) 0731-1420-0

2. Composition/information on ingredients

2.1 Chemical name	content %	symbol	R-phrases	EINECS, ELINCS
Naphtha (petroleum), hydrodesulfurized heavy	80 - 100	Xn	65-66	265-185-4
benzene, mono-C4-9-alkyl derivatives	0,1 < 1	Xn/N	51-53-65-67	272-258-4
2-Ethylhexylnitrate	1 -< 25	Xn	20/21-44	248-363-6

For complete wording of the R-phrases, refer to point 16.

3. Hazards identification

3.1 To people

See point 11 and 15.

Preparation is classified as hazardous in the sense of directive 1999/45/EC.

Risk of explosion if heated under confinement.

Harmful: may cause lung damage if swallowed.

When using: development of flammable vapour/air mixture possible.

3.2 To the environment

See point 12.

4. First aid measures

4.1 Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

4.2 Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

4.3 Skin contact

Wash thoroughly with soap and copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

4.4 Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

2 / 6 EN

Revision: 08.02.2006 Replaces the version of: 21.07.2005 PDF date: 09.02.2006

ProLine Jet Clean Diesel System Reiniger 500ML

Art.: 5154

Danger of aspiration.

4.5 Special resources necessary for first aid

n.g.

5. Fire-fighting measures

5.1 Suitable extinguishing media

CO2

Extinguishing powder

Foam

Cool container at risk with water.

5.2 Extinguishing media which must not be used for safety reasons

High volume water jet

5.3 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Hydrocarbons

Toxic pyrolysis products.

Danger of explosion.

Explosive vapour/air mixture

Dangerous vapours heavier than air.

5.4 Special protective equipment for fire-fighters

Protective respirator with independent air supply

According to size of fire

Full protection, if necessary

5.5 Further information

Dispose of contaminated extinction water according to official regulations.

6. Accidental release measures

Refer to point 13. and for personal protection refer to point 8.

6.1 Personal precautions

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental measures

If leakage occurs, dam up.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods for cleaning up

Collect using absorbant material (e.g. Universal binding medium, sand, kieselguhr) and dispose of according to point 13.

7. Handling and storage

7.1 Handling

Tips for safe handling:

See point 6.1

Ensure good ventilation.

Keep away from sources of ignition - Do not smoke.

Wash hands before breaks and at end of work.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.2. Storage

Requirements for storage rooms and containers:

Store products only unopened, in original packing.

3 / 6 EN

Revision: 08.02.2006 Replaces the version of: 21.07.2005 PDF date: 09.02.2006

ProLine Jet Clean Diesel System Reiniger 500ML

Art.: 5154

Not to be stored in gangways or stair wells.

Observe special storage conditions (in Germany, e.g., in accordance with the regulations in the "Betriebssicherheitsverordnung").

Solvent resistant floor

Do not store with oxidizing agents.

Special storage conditions:

See point 10.2

Store in a well ventilated place.

Protect from direct sunlight and warming.

Store cool

8. Exposure controls/personal protection

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AG values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Chemical Name	Naphtha (petroleum), hydrodesulfurized heavy		
WEL-TWA: 70 ppm (350 mg/m3) (AG)	WEL-STEL: 4 (AG)		---
BMGV: ---		Other information: ---	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AG = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BG = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

8.1 Respiratory protection:

Gas mask filter A (EN 141)

At high concentrations:

Respiratory protection appliance (insulation device) (e.g. EN 137 or EN 138)

8.2 Hand protection:

If applicable

Protective PVC gloves (EN 374)

Protective hand cream recommended.

8.3 Eye protection:

8.4 Skin protection:

If OES or MEL is exceeded.

Solvent resistant protective gloves (EN 374).

Tight fitting protective goggles with side protection (EN 166).

Protective working garments (e.g. safety shoes EN 344, long-sleeved protective working garments)

Additional information on hand protection - No tests have been performed.

Selection made for preparations according to the best available knowledge and information on the ingredients.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of preparations the resistance of glove materials cannot be calculated in advance so it has to be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

9. Physical and chemical properties

Physical state:

Colour:

Odour:

pH-value undiluted:

Boiling point/range (°C):

Melting point/range (°C):

Flash point (°C):

Oxidising properties:

Minimum limit of explosion:

Maximum limit of explosion:

Vapour pressure:

Density (g/ml):

Solubility in water:

Vapour density (air = 1):

Viscosity:

* Naphtha (petroleum), hydrodesulfurized heavy

Liquid

Yellow

Characteristic

n.a.

n.v.

n.v.

63

No

0,6 Vol% *

7,0 Vol% *

n.g.

0,811 (15°C)

Insoluble

Vapours heavier than air.

< 7 mm²/s (40°C)

10. Stability and reactivity

10.1 Conditions to avoid

See point 7

Stable when handled and stored correctly.

Heating, open flame, ignition sources

Pressure increase will result in danger of bursting.

10.2 Materials to avoid

See point 7

Avoid contact with strong oxidizing agents.

10.3 Hazardous decomposition products

See point 5.3

11. Toxicological information

11.1 Acute toxicity and immediate effects

Ingestion, LD50 rat oral (mg/kg):

See point 15.

Inhalation, LC50 rat inhal.(mg/l/4h):

n.v.

Skin contact, LD50 rat dermal (mg/kg):

k.D.v., See point 15.

Eye contact:

n.v.

11.2 Delayed and chronic effects

Sensitization:

n.g.

Carcinogenicity:

n.g.

Mutagenicity:

n.g.

Reproductive toxicity:

n.g.

Narcosis:

n.g.

11.3. Further information

Classification according to calculation procedure.

The following may occur:

Irritation of the eyes

Product removes fat

Dermatitis (skin inflammation)

Ingestion:

Oedema of the lungs

Lung damage

12. Ecological information

Water hazard class (Germany):

2

Self classification:

Yes (VwVwS)

Persistence and degradability:

Readily biodegradable *

Behaviour in sewage plants:

According to the recipe, contains no AOX.

Aquatic toxicity:

n.v.

Ecological toxicity:

n.v.

Accumulation:

Concentration in organisms possible. *

* Naphtha (petroleum), hydrodesulfurized heavy

13. Disposal considerations

13.1. for the material / preparation / residue

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances.

07 07 04 other organic solvents, washing liquids and mother liquors

14 06 03 other solvents and solvent mixes

5 / 6 EN

Revision: 08.02.2006 Replaces the version of: 21.07.2005 PDF date: 09.02.2006

ProLine Jet Clean Diesel System Reiniger 500ML

Art.: 5154

Recommendation:

Pay attention to local and national official regulations

Implement substance recycling.

E.g. suitable incineration plant.

13.2 for contaminated packing material

See point 13.1

Pay attention to local and national official regulations

Empty container completely.

Untaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

14. Transport information

General statements

UN-Number: 3082

Road/Rail-transport (ADR/RID)

Class/packing-group: n.a.

Classification code: n.a.

LQ: n.a.

Transport by sea

IMDG-code: 9/III (class/packing-group)

EmS: F-A, S-F

Marine Pollutant: Yes

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ALKYL (C3-5) BENZENE)

Limited Quantities



Transport by air

IATA: 9/-/III (class/secondary danger/packing-group)

Environmentally hazardous substance, liquid, n.o.s. (ALKYL (C3-5) BENZENE)

Additional information:

Danger code and packing code on request.

15. Regulatory information

Classification according to Dangerous Product Regulations incl. EC Directives (67/548/EEC and 1999/45/EC)

Symbols: Xn

Indications of danger:

Harmful



R-phrases:

44 Risk of explosion if heated under confinement.

65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

S-phrases:

2 Keep out of the reach of children.

15 Keep away from heat.

23.f Do not breathe vapour/spray.

24 Avoid contact with skin.

35 This material and its container must be disposed of in a safe way.

62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Additions:

Naphtha (petroleum), hydrodesulfurized heavy

Observe restrictions: Yes

Observe restrictive guidelines 76/769/EEC, 1999/51/EC, 1999/77/EC

VOC 1999/13/EC k.D.v.

16. Other information

These details refer to the product as it is delivered.

Storage class VCI (Germany): 3 B

Revised points: 14

The following phrases represent the prescribed R-phrases for the ingredients (designated in point 2).

6 / 6 EN

Revision: 08.02.2006 Replaces the version of: 21.07.2005 PDF date: 09.02.2006

ProLine Jet Clean Diesel System Reiniger 500ML

Art.: 5154

- 65 Also harmful: may cause lung damage if swallowed.
66 Repeated exposure may cause skin dryness or cracking.
51 Toxic to aquatic organisms.
53 May cause long-term adverse effects in the aquatic environment.
67 Vapours may cause drowsiness and dizziness.
20/21 Harmful by inhalation and in contact with skin.
44 Risk of explosion if heated under confinement.

Legend:

n.a. = not applicable / n.v., k.D.v. = not available / n.g. = not checked

OES = Occupational exposure standard / MEL = Maximum exposure limit / BMGV = Biological monitoring guidance value

AG = "Arbeitsplatzgrenzwert" (workplace limit value, Germany) / BG = "Biologischer Grenzwert" (biological limit value, Germany)

VbF = Regulations for flammable liquids (Austria)

WGK = water hazard class (Germany) - WGK 3 = very hazardous, WGK 2 = hazardous, WGK 1 = slightly hazardous to water

VOC = Volatile organic compounds / AOX = Adsorbable organic halogen compounds

VwVwS = Administrative Order relating to substances hazardous to water (Germany)

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Beim Staumberge 3, D-32839 Steinheim, Tel.: 01805-CHEMICAL / 01805-243 642, Fax: 05233-941790

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.